


Mortise Glass Lock

Model 62 Magnalock

Security and Life Safety

- Over 1200 pounds of certified electromagnetic holding power.
- Measures: 8" x 3" x 1 3/4"
- Efficient 3-watt power consumption. (125 mA at 24VDC, or 250 mA at 12VDC.)
- UL recognized for use on emergency exit doors.
- Instantaneous unlocking with no residual magnetism.
- Fail-safe design, however, a small battery will run lock for hours.
- Optional SENSTAT™ lock status sensor assures the lock is holding at full force.
- Vandal and weather resistant with attractive stainless steel case.
- Brushed stainless steel, for special finish applications use dress covers.



Mfg #	Voltage	EZ #
<i>Standard Model</i>		
SN62 12/24VDC	12/24VDC	069376
<i>F – Face drilled for inswinging door (order with z bracket)</i>		
SN62F 12/24VDC	12/24VDC	069378
<i>GF – Face drilled w/conduit fitting (order with z bracket), 1/2" ID, 3/4" OD pipe thread</i>		
SN62GF 12/24VDC	12/24VDC	069380
<i>G – Conduit fitting, universal (1/2" ID, 3/4" OD pipe thread)</i>		
SN62G 12/24VDC	12/24VDC	069379
<i>SC – Senstat-form C</i>		
SN62SC 12/24VDC	12/24VDC	069746

Model 32 MiniMag

Traffic Control

- Over 600 pounds of certified electromagnetic holding power
- Suitable for traffic control - not intended for security doors
- Compact size: 8" x 1 7/8" x 1 1/2"
- Vandal and weather resistant stainless steel case
- Efficient 3.5 watt power consumption. (150 mA at 24 VDC, or 300 mA at 12 VDC)



Mfg #	Voltage	EZ #
<i>Standard Model</i>		
SN32 12VDC	12VDC	028117
SN32 24VDC	24VDC	028116
<i>F - Face drilled for inswing door (order w/z-bracket)</i>		
SN32F 12VDC	12VDC	042025
SN32F 24VDC	24VDC	042026

Mortise Glass Lock

- Electric locking for narrow stile aluminum frame glass doors
- Installs in existing ANSI opening
- Fail secure • UL Listed
- Accepts 1" mortise cylinder for mechanical override



Mfg # SNMGL24 (24VDC) EZ # 080704

Model 82 Magnalock

Highest Security Needs

- Over 1,800 pounds of electromagnetic holding force.
- Vandal/Weather resistant stainless steel case.
- Efficient 4-watt power consumption, (175 mA @ 24 VDC, 350 mA @ 12 VDC).
- New Senstat lock status design included, SPDT dry output. Switches when lock loses power and/or the armature loses contact.
- New solid state patented instant release/noise suppression circuit. No suppression electronics needed for sensitive access control/alarm equipment.
- Measures: 12" x 3" x 1 3/4"



Mfg #	Voltage	EZ #
SNM82SC12/24VDC	12/24VDC	068376

Magnalock Accessories

Dress Covers

Mfg # SNDC62BK	Black anodized	EZ # 013337
Mfg # SNDC62BP	Polished Brass	EZ # 028077

Z-Bracket For Inswinging Door

(includes fasteners & cover)

Mfg # SNZ62CL	Clear anodized	EZ # 013348
Mfg # SNZ32CL	Clear anodized	EZ # 029208

Universal Header Brackets (1" x 9 1/2" x 1 1/2")

Mfg # SNUHB CL	Clear anodized	EZ # 028193
----------------	----------------	-------------

NOTE: 1" and/or 1 1/2" extension. Room for wire splicing.

Aluminum (Spacer) Bracket

Mfg # SNASB32CL	For 32 lock (clear)	EZ # 067021
Mfg # SNASB62CL	For 62 lock (clear)	EZ # 067022

Header Extension Brackets


Mfg # SNHEB 2CL	2" x 2" x 8"	EZ # 013345
Mfg # SNHEB 3CL	3" x 3" x 8"	EZ # 027592

Replacement Strike Plate


Mfg # SNASS82	Split strike set (82 lock)	EZ # 067023
Mfg # SNAPS62	Strike Plate for 62	EZ # 042031

Stop Filler Plates

Mfg # SNSFP 1/2CL	1/2" x 1 1/4" x 8"	EZ # 027597
Mfg # SNSFP 5/8CL	5/8" x 1 1/4" x 8"	EZ # 027598




UHB




HEB


ASS82



SFP



ASB



Digital Entry System (DK-26)

- High Security Keypad. Central Processor Unit mounts inside the protected area. Attacking the keypad will not release the lock.
- Rugged Cast stainless steel keypad fits narrow stile frames. Standard and tamper proof screws provided. Ideal for high traffic installations.
- 59 Codes. • Powerful Features. Easy to install, program and operate.
- Operates on 12 or 24 Volts, AC or DC. Operates any electric lock/gate (5 amp max). Lock release adjustable from 1 to 99 seconds or in toggle (on/off) mode. Exit request input (REX) standard.
- Includes signaling LEDs and audible output. Can be modified for quiet operation or specialized applications.
- True 10 digit code operation. Millions of code possibilities • Built-in doorbell and alarm functions.
- Non-Volatile EEPROM programming and user code memory
- Heavy duty spy shield available on special order



Mfg. #	Description	EZ #
SNDK26SS	Keypad Access System	060615
SNDK26BK	Keypad Access System (black)	060617
SNDK26PSS	Keypad Only	060616

Stand Alone Digital Entry (DK-11)

- Durable American Made keypad with numbers that won't wear off • Ideal for high traffic installations
- Heavy duty stainless steel face plate • Flush mount back box with both standard and tamper proof screws
- Four entry codes – 2 to 7 digits in length. Millions of code possibilities • True 12 digit keypad
- Exit request input (REX) • Non-volatile EEPROM memory storage without the use of batteries

Mfg # SNDK11 EZ # 031185



TSB3 Touch Sense Bar™

The TSB3 is the perfect exit device to meet the prior knowledge for use requirement. Using patented technology, the simple act of touching the bar (even through gloves or clothing) trips an electronic sensor which immediately releases the electric lock.

Many card reader applications call for free egress which requires a request-to-exit signal to the control electronics. Activating the TSB energizes a DPDT 2Amp relay which both releases the lock and signals the access control system. For even greater flexibility, the sensor operates on 12-24 volts, DC.

The TSB outperforms mechanical products, including switch-equipped panic bars. There are no moving parts to wear out and no requirements for periodic maintenance or replacement. In the unlikely event of sensor failure, there is a redundant push switch mounted on the rear of the bar.



Mfg # SNTSB3CL	Alum. Touch Sense Bar	EZ # 042041
Mfg # SNTSB3BK	Black Touch Sense Bar	EZ # 042042
Mfg # SNTS3	Replacement Sensor(TSB3)	EZ # 061991
Mfg # SNTSB C	Door Cord	EZ # 061990
Mfg # SNTS2	Rep. Sensor for TSB1	EZ # 029173


- Length of bar can be field modified. Supplied for 36" wide door (up to 48" is available by special order)
- Not handed
- Comes with mounting fasteners and door cord
- UL Listed as part of Exit Control System

Touch Sense Handle

Unique Touch Sense Technology in a Convenient Handle Design for Releasing any Electromagnetic Lock.

- Simple act of grabbing or pushing on the handle releases the electromagnetic lock.
- Dual redundancy switch built-in. • Engraved plates indicating Pull or Push with blank plates in Black or Gray.
- 16 feet of cable with connector provided. Door cord included.

Mfg # SNTSH CL	Alum Touch-Sense Handle	EZ # 062461
Mfg # SNTSH BK	Black Touch-Sense Handle	EZ # 062462





Exit Buttons

PB Series (special duty 7 Amp)

Round 1 1/2" illuminated button 12/24VDC.

Mfg # SNPB Momentary, single gang EZ # 027874

PB2 Series (heavy duty 10 Amp)

Square 2" illuminated button, 12/24VDC. SPDT contacts.

Mfg # SNPB2 Momentary, single gang EZ # 027740

PB3 Series (general duty 3 Amp N.O.& N.C. contacts)

Rectangular 3/4" x 1" illuminated button, 12/24VDC.

Mfg # SNPB3N Momentary, narrow EZ # 028731



PB



PB2



EEB2



PB3

PB2E Series (heavy duty 10 Amp SPDT contacts)

Square 2" button - non-illuminated. Backbox not included.

Mfg # SNPB2E Momentary, single gang EZ # 027741

EEB2 Series (3 Amp SPDT contacts)

Emergency Exit button

Single gang

Mfg # SNEEB2 EZ # 067612

MK Series (mortise) UL Listed Key Switches

Accepts a user supplied mortise cylinder. (1 1/8" or 1 1/4") and can use 1 (included) or 2 (optional) switches. Bi-color LED, 12/24VDC.

Momentary, single gang

Mfg # SNMK EZ # 028798

Alternate, single gang

Mfg # SNMKA EZ # 046261

Momentary, narrow style

Mfg # SNMKN EZ # 028799

Alternate, narrow style

Mfg # SNMKAN EZ # 029210

Momentary, replacement switch only

Mfg # SNMKS EZ # 029175



XDT Series Exit Delay Timer

Designed to meet NFPA-101 Life Safety Code, for special locking arrangements. Requires regulated DC voltage.

Mfg # SNXDT24 24VDC EZ # 061987

Time delay module in metal enclosure

Mfg # SNBAXDT24 24VDC EZ # 029129



XDT24

Prime Time Digital Timer

7 day digital programmable timer 12/24VAC or VDC operation. 10Amp DPDT contacts.

Mfg # SNDT7 EZ # 027586



DT7

Motion Detector

Passive infrared request-to-exit device for magnetic lock release. Operates 12 to 24 VDC (filtered or regulated)

Mfg # SNXMS EZ # 065795



BR-7 Bridge Rectifier

Potted with 4 color coded leads 7 amp cap. Converts AC to DC voltage. 12 or 24VDC

Mfg # SNBR7 EZ # 013335



TM-9 Timemate Timer

Release hold timer, SPDT 3 amp contacts, non retriggerable input, 1-36 Sec. adjustable, 12/24VDC, 24VAC.

Mfg # SNTM9 EZ # 028372

BPS Series Power Supplies

- Regulated DC power supply • Battery charging capability
- Fused AC inputs • Fire alarm interface
- All UL components • LED power indicator

Mfg # EZ # Amp

Mfg #	EZ #	Amp
<i>12VDC, 12" x 9" x 4"</i>		
SNBPS12 1	013333	1
<i>12VDC, 14" x 14" x 4"</i>		
SNBPS12 3	042022	3
<i>24VDC, 12" x 9" x 4"</i>		
SNBPS24 1	060204	1
<i>24VDC, 14" x 14" x 4"</i>		
SNBPS24 2	029176	2
SNBPS24 3	042023	3
<i>24VDC, 15" x 18" x 6"</i>		
SNBPS24 6	029130	8



Unlatch

Releases latch by pushing it out of the strike while at the same time maintaining deadlatch security. Will operate under 30 pounds of pre-load and guaranteed to maintain a sound strike mechanism under rigorous use.

Mfg # SNUNL12 (12VDC) EZ # 067884

Mfg # SNMUNL12 (mort.12VDC) EZ # 075914

Mfg # SNMUNL24 (mort. 24VDC) EZ # 075867



Shear Aligning Magnalock

Permits concealed mounting in aluminum, wood and steel doors for the ultimate in finished appearance. Both the magnet and strike plate assembly takes up only 1 1/2" width in the door and door frame.

Mfg # SNSAM EZ # 067882

With Senstat

Mfg # SNSAMSC EZ # 067883

